

LUBRIFICANTI RACCOMANDATI

PARTICOLARI		MOBIL	SHELL	ESSO	B.P.	CASTROL	DUCKHAM'S	CALTEN TEXACO	S.A.E. & A.P.I. DESIGNAZIONE
MOTORE	temperatura in C° superiore a 27°	Mobiloil A.F.	X-100 Multigrade 20W/40 o X-100 40	Esso Extra Motor Oil 20W/40 o Esso Motor Oil 40	Energol Motor Oil 40	Castrol XXL	Q20-50 Duckham's Nol "Forty"	Havoline 40 o Havoline Special 20W/40	S.A.E. 40 M.M.
	da 0° — 27°	Mobiloil A	X-100 Multigrade 10W/30 Shell X-100 30W	Esso Extra Motor Oil 10W/30 Esso Motor Oil 30	Energol Motor Oil 30	Castrol XL	Q5500 Duckham's Nol "Thirty"	Havoline Special 10W/30 Havoline 30	S.A.E. 30 M.M.
	inferiore a 0°	Mobiloil Arctic	X-100 Multigrade 10W/30 Shell X-100 20W	Esso Extra Motor Oil 10W/30 Esso Motor Oil 20	Energol Motor Oil 20W	Castrolite	Q5500 Duckham's Nol "Twenty"	Havoline Special 10W/30 Havoline 20/20W	S.A.E. 20W M.M.
OLIO PER RODAGGIO		Mobil Upperlube	Shell Donax U	Esso Upper Motor Lubricant	Energol U.C.L.	Castrollo	Duckham's Adcoids	Upper Cylinder Lubricant	
AMMORTIZZATORI DEI CARBURATORI		UTILIZZARE L'OLIO ADATTO PER OGNI CASO							
SCATOLA CAMBIO	fino a 0°	Mobilube GX.90	Shell Spirax 90 E.P.	Esso Gear Oil G.P.90	Energol E.P. S.A.E. 90	Castrol Hypoy	Duckham's Hypoid 90	Universal Thuban 90	G.L.4 Hypoid 90
PONTE POSTERIORE	sotto a 0°	Mobilube GX.80	Shell Spirax 80 E.P.	Esso Gear Oil G.P.80	Energol E.P. S.A.E. 80	Castrol Hypoy Light	Duckham's Hypoid 80	Universal Thuban 80	G.L.4 Hypoid 80
SCATOLA STERZO DA INIETTARE A PRESSIONE		Mobilgrease M.P.	Shell Retinax A	Esso Multi-Purpose Grease H	Energrease L2	Castrol L.M.	Duckham's L.B.10	Marfak Multipurpose 2	
OLIO PER OLIATORE A MANO		Mobil Handy Oil	Shell X-100 20W	Esso Handy Oil	Energol Motor Oil S.A.E. 20W	Everyman Oil	Duckham's General Purpose Oil	Lubrificante Home	
BALESTRA POSTERIORE		OLIO USATO PER MOTORE O PONTE POSTERIORE							
CAVO FRENO A MANO		Mobilgrease M.P.	Shell Retinax A	Esso Multi-Purpose Grease H	Energrease L.2	Castrol grasso percavi	Duckham's Keenol KG 16	Marfak Multipurpose 2	
OLIO PER FRENO IDRAULICO E COMANDO FRIZIONE		FLUIDO CASTROL GIRLING PER FRENI E FRIZIONI IDRAULICHE				QUANDO NON SI PUÒ AVERE QUESTA MARCA, USARE OLII CHE ABBIANO DENSITÀ S.A.E.70 R3			
SOLUZIONI ANTICONGELANTI		B.P. Anti-frost	Mobil Permazone	Shell Anti-freeze	Esso Anti-freeze	Castrol Anti-freeze	Duckham's Anti-freeze	Smith's Bluecol	

SCHEMA DI LUBRIFICAZIONE E MANUTENZIONE

